

IN THE CLAIMS:

Claim 1 (original): A sensor for determining flow rate of a fluid through a volume, comprising:

a thermistor at least partially inserted into the volume; and

a sensor circuit adapted to cycle the thermistor between a zero-power mode and a self-heated mode.

Claim 2 (original): The sensor as recited in claim 1, wherein the sensor circuit comprises a configurable power controller adapted to cycle the thermistor between a zero-power mode and a self-heated mode.

Claim 3 (original): The sensor as recited in claim 2, wherein the configurable power controller comprises:

a variable resistance; and

a switch in association with the variable resistance, the switch being adapted to cycle the variable resistance between a first value and a second value, the first value being selected to operate the thermistor in the zero-power mode and the second value being selected to operate the thermistor in the self-heated mode.

Claim 4 (original): The sensor as recited in claim 3, wherein the thermistor is in series with the variable resistance between a first side of a power source and a second side of a power source.

Claim 5 (original): The sensor as recited in claim 4, wherein the thermistor is arranged in series with the variable resistance at the high side of the power source.

Claim 6 (original): The sensor as recited in claim 4, wherein the thermistor is arranged in series with the variable resistance at the low side of the power source.

Claim 7 (original): The sensor as recited in claim 1, further comprising a conversion circuit for use in measuring the voltage drop across the thermistor.

Claim 8 (original): The sensor as recited in claim 7 6, wherein the conversion circuit comprises a first channel for measuring the voltage drop across the thermistor when the thermistor is in its zero-power mode and a second channel for measuring the voltage drop across the thermistor when the thermistor is in its self-heated mode.

Claim 9 (previously presented): The sensor as recited in claim 8, wherein each channel comprises an isolation amplifier.

Claim 10 (previously presented): The sensor as recited in claim 8, wherein the second channel comprises a voltage divider for scaling down the voltage drop across the thermistor.

Claim 11 (original): The sensor as recited in claim 6, wherein the conversion circuit is adapted to convert the voltage drop across the thermistor from logarithmic scale.

Claim 12 (original): The sensor as recited in claim 6, wherein the conversion circuit comprises a micro-controller adapted to convert the voltage drop across the thermistor in the zero-power mode and the voltage drop across the thermistor in the self-heated mode to the flow rate of the fluid through the volume.

Claim 13 (original): The sensor as recited in claim 3, wherein:

the variable resistance comprises a first fixed resistor in series with a second fixed resistor; and
the switch comprises a transistor in parallel with the first fixed resistor such that the transistor is operable to bypass the first fixed resistor.

Claim 14 (original): The sensor as recited in claim 2, wherein the configurable power controller comprises a configurable constant current source adapted to cycle the thermistor between a zero-power mode and a self-heated mode.

Claim 15 (original): The sensor as recited in claim 1, wherein the sensor circuit further comprises a reference circuit adapted to store a zero-power voltage as a reference value.

Claim 16 (original): The sensor as recited in claim 15, wherein in the self-heated mode a known pulse of heat is injected into the thermistor for a predetermined period of time.

Claim 17 (original): The sensor as recited in claim 16, wherein the sensor circuit further comprises a comparison circuit that compares the stored reference value with a changing zero-power voltage value associated with the dissipation of the injected known pulse of heat into the flowing fluid.

Claim 18 (original): The sensor as recited in claim 17, wherein the sensor circuit further comprises a timer circuit that measures the time required for the stored reference value to substantially equal the changing zero-power value associated with the dissipating injected pulse of heat.

Claim 19 (original): The sensor as recited in claim 18, wherein the sensor circuit further comprises an offset circuit that adds an offset voltage value to the stored reference value thereby accommodating for variations in the ambient temperature of the flowing fluid.

Claim 20 (original): The sensor as recited in claim 18, further comprising a conversion circuit adapted to convert the stored reference value, the time required to dissipate the known injected pulse of heat into the flowing fluid, and thermal properties of the fluid to the flow rate of the fluid through the volume.

Claim 21 (original): The sensor as recited in claim 2, wherein the configurable power controller comprises a configurable constant voltage source adapted to cycle the thermistor between a zero-power mode and a self-heated mode.

Claims 22-30 (canceled).